

# Acton

7062.01 - 7062.40



## Product

### Upholstery

## Description

**Strong upholstery fabric in a melange look, in a wide range of colours**

## Composition

**87% recycled polyester FR / 13% polyester FR**

## Width

**± 141 cm, ± 56 inches**

## Weight

**± 605 gr/m<sup>2</sup>, ± 20 oz/yd<sup>2</sup>**

## Flame retardancy

**BS 5852 , Crib 5  
Cal TB 117-2013, section 1 , Pass  
DIN 4102 , B1  
EN 1021/1-2 , Pass  
IMO 2010 FTP part 8 , Pass  
NF P 92/503-507 , M1  
NFPA 260 , Class 1  
UNI 9175 , Classe 1**

## Abrasion

**ASTM D3597/D4157 (#10 cotton duck) ,  
100.000 double rubs Wyzenbeek  
ISO 12947-2 , 90.000 rubs Martindale**

## Pilling

**ASTM D3511  
5 (scale 1-5)  
ISO 12945-2  
4 (scale 1-5)**

## Colorfastness to crocking

**AATCC 8  
5 (scale 1-5) wet / 5 (scale 1-5) dry  
ISO 105 X12  
4-5 (scale 1-5) wet / 4-5 (scale 1-5) dry**

## Colorfastness to light

**AATCC 16.2 opt.1 or 16.3 opt. 3  
4 (scale 1-5)  
ISO 105 B02  
6 (scale 1-8)**

## Seam slippage

**ASTM D4034  
109 lbs warp / 86 lbs weft  
ISO 13936-2  
3.7 mm warp / 3.7 mm weft**

## Breaking strength

**ASTM D5034  
263 lbs warp / 345 lbs weft  
ISO 13934-1  
1380 N warp / 1790 N weft**

## Labels



## Care & Maintenance



## Shrinkage

**Shrinkage 70°  
-2.7% warp / -0.6% weft**

# Acton

7062.01 - 7062.40

---

