

Acton

7062.01 - 7062.40



Product

Meubelbekleding

Omschrijving

Sterke meubelstof in melange optiek, in breed kleurengamma

Samenstelling

87% recycled polyester FR / 13% polyester FR

Breedte

± 141 cm, ± 56 inches

Gewicht

± 605 gr/m¹, ± 20 oz/yd¹

Brandwerendheid

**BS 5852 , Crib 5
Cal TB 117-2013, section 1 , Pass
DIN 4102 , B1
EN 1021/1-2 , Pass
IMO 2010 FTP part 8 , Pass
NF P 92/503-507 , M1
NFPA 260 , Class 1
UNI 9175 , Classe 1**

Slijtvastheid

**ASTM D3597/D4157 (#10 cotton duck) ,
100.000 double rubs Wyzenbeek
ISO 12947-2 , 90.000 rubs Martindale**

Pilling

**ASTM D3511
5 (scale 1-5)
ISO 12945-2
4 (scale 1-5)**

Wrijftechtheid

**AATCC 8
5 (scale 1-5) wet / 5 (scale 1-5) dry
ISO 105 X12
4-5 (scale 1-5) wet / 4-5 (scale 1-5) dry**

Lichtechtheid

**AATCC 16.2 opt.1 or 16.3 opt. 3
4 (scale 1-5)
ISO 105 B02
6 (scale 1-8)**

Naadschuifweerstand

**ASTM D4034
109 lbs warp / 86 lbs weft
ISO 13936-2
3.7 mm warp / 3.7 mm weft**

Treksterkte

**ASTM D5034
263 lbs warp / 345 lbs weft
ISO 13934-1
1380 N warp / 1790 N weft**

Keurmerken



USCG -
EU MRA
0038



STANDARD
100
507-0023
Hohenstein HTTI

Reiniging & Onderhoud



Krimp

**Shrinkage 70°
-2.7% warp / -0.6% weft**

Acton

7062.01 - 7062.40



7062.01



7062.02



7062.03



7062.04



7062.05



7062.06



7062.07



7062.08



7062.09



7062.10



7062.11



7062.12



7062.13



7062.14



7062.15



7062.16



7062.17



7062.18



7062.19



7062.20



7062.21



7062.22



7062.23



7062.24



7062.25



7062.26



7062.27



7062.28



7062.29



7062.30



7062.31



7062.32



7062.33



7062.34



7062.35



7062.36



7062.37



7062.38



7062.39



7062.40