

Arches

7066.01 - 7066.17



Product

Upholstery

Description

Dynamic textile weave structure

Composition

Vinyl coat on a cotton/polyester backing

Width

± 137-140 cm, ± 54-55 inches

Weight

± 800 gr/m², ± 36 oz/yd¹

Flame retardancy

BS 5852 , Crib 5

Cal TB 117-2013, section 1 , Pass

DIN 4102 , B2

EN 1021/1-2 , Pass

IMO 2010 FTP part 8 , Pass

NF P 92/503-507 , M2

NFPA 260 , Class 1

Abrasion

ASTM D3597/D4157 (#10 cotton duck) ,

100.000 double rubs Wyzenbeek

ISO 12947-2 , > 300.000 rubs Martindale

Colorfastness to crocking

AATCC 8

5 (scale 1-5) wet / 5 (scale 1-5) dry

ISO 105 X12

5 (scale 1-5) wet / 5 (scale 1-5) dry

Colorfastness to light

ISO 105 B02

7 (scale 1-8)

Labels




USCG –
EU MRA
0038


vinyl^{plus}
COMMITTED TO
SUSTAINABLE DEVELOPMENT

Arches


7066.01 - 7066.17




7066.01




7066.02




7066.03




7066.04




7066.05




7066.06



7066.07



7066.08



7066.09



7066.10



7066.11




7066.12



7066.13




7066.14



7066.15



7066.16



7066.17