

Auckland

7071.01 – 7071.34



Product

Upholstery

Description

A boucle upholstery fabric with a two-tonal, playful, non-directional grid

Composition

76% recycled polyester FR / 24% polyester FR

Width

± 141 cm, ± 56 inches

Weight

± 704 gr/m², ± 23 oz/yd²

Flame retardancy

**BS 5852 , Crib 5
Cal TB 117-2013, section 1 , Pass
DIN 4102 , B1
EN 1021/1-2 , Pass
IMO 2010 FTP part 8 , Pass
NF P 92/503-507 , M1
NFPA 260 , Class 1**

Abrasion

**ASTM D3597/D4157 (#10 cotton duck) ,
80.000 double rubs Wyzenbeek
ISO 12947-2 , 60.000 rubs Martindale**

Pilling

**ASTM D3511
5 (scale 1-5)
ISO 12945-2
4 (scale 1-5)**

Colorfastness to crocking

AATCC 8

5 (scale 1-5) wet / 5 (scale 1-5) dry

ISO 105 X12

4-5 (scale 1-5) wet / 4-5 (scale 1-5) dry

Colorfastness to light

AATCC 16.2 opt.1 or 16.3 opt. 3

5 (scale 1-5)

ISO 105 B02

6 (scale 1-8)

Seam slippage

ASTM D4034

128 lbs warp / 112 lbs weft

ISO 13936-2

3 mm warp / 3 mm weft

Breaking strength

ASTM D5034

220 lbs warp / 402 lbs weft

ISO 13934-1

1550 N warp / 2500 N weft

Labels



USCG -
EU MRA
0038



STANDARD
100
S21-3365
Hohenstein HTTI

Care & Maintenance



Shrinkage

Shrinkage 70°

-2.4% warp / -1.4% weft

Auckland

7071.01 – 7071.34

