

Bedra

8059.01 - 8059.33



Product

Curtain

Description

Unpatterned curtain fabric, dim out

Composition

45% recycled polyester FR / 55% polyester FR

Width

± 295 cm, ± 116 inches

Weight

± 782 gr/m², ± 25 oz/yd²

Sound absorption

ISO 354, alpha w

0.70

Visual & Thermal comfort

AATCC 148

Test available

EN 410/EN 14501

Test available

Flame retardancy

BS 5867-2 , Type C

CAN/ULC S109 , Pass

DIN 4102 , B1

EN 13773 , Class 1

IMO 2010 FTP part 7 , Pass

NF P 92/503-507 , M1

NFPA 701 (meth. 1 or 2) , Pass

Übereinstimmung , Pass

UNI VF 8456-8457 , Classe 1

Colorfastness to crocking

AATCC 8 (solids)

5 (scale 1-5) wet / 5 (scale 1-5) dry

ISO 105-X12

5 (scale 1-5) wet / 5 (scale 1-5) dry

Colorfastness to light

AATCC 16.2 option 1 or 16.3 opt 3

4-5 (scale 1-5)

ISO 105-B02

6 (scale 1-8)

Seam slippage

ASTM D434

43.5 lbs warp / 48 lbs weft

Labels



USCG -
EU MRA
0038



STANDARD
100
507-0023
Hohenstein HTTI



Baustoffklasse schwerenflammbar
DIN 4102, B1

Care & Maintenance



Shrinkage

Shrinkage 30°

-0.4% warp / -1.4% weft

Shrinkage 70°

-2.5% warp / -1.5% weft

Bedra

8059.01 - 8059.33

