

Bedra+Print

8061.01



Produit

Tissus pour rideaux

Description

Rideau imprimable obscurcissant soyeux

Composition

100% polyester ignifuge

Largeur

± 290 cm, ± 114 inches

Poids

± 782 gr/m¹, ± 25 oz/yd¹

Absorption acoustique

ISO 354, alpha w

0.70

Confort Visuel & Thermique

AATCC 148

Test available

EN 410/EN 14501

Test available

Non feu

BS 5867-2 , Type C

CAN/ULC S109 , Pass

DIN 4102 , B1

EN 13773 , Class 1

IMO 2010 FTP part 7 , Pass

NF P 92/503-507 , M1

NFPA 701 (meth. 1 or 2) , Pass

Übereinstimmung , Pass

UNI VF 8456-8457 , Classe 1

Résistance au frottement

AATCC 8 (solids)

5 (scale 1-5) wet / 5 (scale 1-5) dry

ISO 105-X12

5 (scale 1-5) wet / 5 (scale 1-5) dry

Solidité lumière

AATCC 16.2 option 1 or 16.3 opt 3

4-5 (scale 1-5)

ISO 105-B02

6 (scale 1-8)

Résistance au glissement à la couture

ASTM D434

43.5 lbs warp / 48 lbs weft

Étiquettes



USCG -
EU MRA
0038



STANDARD
100
507-0023
Hohenstein HTI



Baustoffklasse schwerentflammbar
DIN 4102, B1

Entretien & Maintenance



Rétrécissement

Shrinkage 30°

-0.4% warp / -1.4% weft

Shrinkage 70°

-2.5% warp / -1.5% weft

Bedra+Print

8061.01



8061.01