


Capri

8056.01 - 8056.12



Product
Curtain

Description
Unpatterned, uni half transparent acoustic curtain fabric

Composition
100% flame retardant polyester

Width
± 306 cm, ± 120 inches

Weight
± 303 gr/m², ± 10 oz/yd²

Sound absorption
ISO 354, alpha w
0.65 (pleated)
ASTM C423, nrc
0.70


Visual & Thermal comfort
EN 410/EN 14501
Test available

Flame retardancy
NFPA 701 (meth. 1 or 2) , Pass
EN 13773 , Class 1
BS 5867-2 , Type C
NF P 92/503-507 , M1
DIN 4102 , B1
Übereinstimmung , Pass
UNI VF 8456-8457 , Classe 1
CAN/ULC S109 , Pass

Colorfastness to crocking
ISO 105-X12
wet 4-5 (scale 1-5) / dry 4-5 (scale 1-5)
AATCC 8 (solids)
wet 5 (scale 1-5) / dry 5 (scale 1-5)

Colorfastness to light
ISO 105-B02
6 (scale 1-8)
AATCC 16.2 option 1 or 16.3 opt 3
4-5 (scale 1-5)

Labels




Care & Maintenance



Shrinkage
Shrinkage 30° warp 0% / weft -0.6%
Shrinkage 70° warp -0.6% / weft -1.2%

Capri

8056.01 - 8056.12



8056.03




8056.01




8056.02




8056.04



8056.05




8056.06




8056.07




8056.08




8056.09



8056.10



8056.11



8056.12