

Chira

8053.01 - 8053.32



Product

Curtain

Description

Fine transparency with subtle vertical effect

Composition

100% flame retardant polyester

Width

± 317 cm, ± 125 inches

Weight

± 143 gr/m¹, ± 5 oz/yd¹

Visual & Thermal comfort

EN 410/EN 14501

Test available

Flame retardancy

BS 5867-2 , Type C

CAN/ULC S109 , Pass

DIN 4102 , B1

EN 13773 , Class 1

IMO 2010 FTP part 7 , Pass

NF P 92/503-507 , M1

NFPA 701 (meth. 1 or 2) , Pass

Übereinstimmung , Pass

UNI VF 8456-8457 , Classe 1

Colorfastness to crocking

AATCC 8 (solids)

5 (scale 1-5) wet / 5 (scale 1-5) dry

ISO 105-X12

4-5 (scale 1-5) wet / 4-5 (scale 1-5) dry

Colorfastness to light

AATCC 16.2 option 1 or 16.3 opt 3

4-5 (scale 1-5)

ISO 105-B02

6 (scale 1-8)

Labels



USCG -
EU MRA
0038



STANDARD
100
S07-0023
Hohenstein HTTI



Boustoffklasse schwerentflammbar
DIN 4102, B1

Care & Maintenance



Shrinkage

Shrinkage 30°

-0.5% warp / -0.3% weft

Shrinkage 70°

-0.8% warp / -0.5% weft

Chira

8053.01 - 8053.32

