

Clare

8052.01 - 8052.24



Producto

Cortinas

Descripción

Estructura de malla transparente abierta

Composición

100% poliéster ignífugo

Anchura

± 300 cm, ± 118 inches

Peso

± 174 gr/m¹, ± 6 oz/yd¹

Confort Visual & Térmico

EN 410/EN 14501

Test available

Combustión retardada

BS 5867-2 , Type C

CAN/ULC S109 , Pass

DIN 4102 , B1

EN 13773 , Class 1

IMO 2010 FTP part 7 , Pass

NF P 92/503-507 , M1

NFPA 701 (meth. 1 or 2) , Pass

Übereinstimmung , Pass

UNI VF 8456-8457 , Classe 1

Resistencia al frotamiento

AATCC 8 (solids)

5 (scale 1-5) wet / 5 (scale 1-5) dry

ISO 105-X12

4-5 (scale 1-5) wet / 4-5 (scale 1-5) dry

Insensibilidad a la luz

AATCC 16.2 option 1 or 16.3 opt 3

5 (scale 1-5)

ISO 105-B02

6 (scale 1-8)


Etiquetas



USCG -
EU MRA
0038



STANDARD
100
507-0023
Hohenstein RTTI



Baustoffklasse schwerentflammbar
DIN 4102, B1

Cuidado & Mantenimiento



Contracción

Shrinkage 30°

-1.6% warp / -1.4% weft

Shrinkage 70°

-2% warp / -2% weft

Clare

8052.01 - 8052.24



8052.01



8052.02



8052.03



8052.04



8052.05



8052.06



8052.07



8052.08



8052.09



8052.10



8052.11



8052.12



8052.13



8052.14



8052.15



8052.16



8052.17



8052.18



8052.19



8052.20



8052.21



8052.22



8052.23



8052.24