

Colour Connect

7078.01 - 7078.43



Product

Upholstery

Description

Plain upholstery fabric in a large colour range

Composition

100% recycled polyester FR

Width

± 150 cm, ± 59 inches

Weight

± 435 gr/m², ± 14 oz/yd²

Flame retardancy

BS 5852 , Crib 5

Cal TB 117-2013, section 1 , Pass

DIN 4102 , B1

EN 1021/1-2 , Pass

IMO 2010 FTP part 8 , Pass

NF D 60-013 , Pass

NFPA 260 , Class 1

Abrasion

ASTM D3597/D4157 (#10 cotton duck) ,

100.000 double rubs Wyzenbeek

ISO 12947-2 , 60.000 rubs Martindale

Pilling

ASTM D3511

5 (scale 1-5)

ISO 12945-2

4-5 (scale 1-5)

Colorfastness to crocking

AATCC 8

5 (scale 1-5) wet / 5 (scale 1-5) dry

ISO 105 X12

4-5 (scale 1-5) wet / 4-5 (scale 1-5) dry

Colorfastness to light

AATCC 16.2 opt.1 or 16.3 opt. 3

5 (scale 1-5)

ISO 105 B02

6 (scale 1-8)

Seam slippage

ASTM D4034

121 lbf warp / 109 lbf weft

ISO 13936-2

3.3 mm warp / 2.3 mm weft

Breaking strength

ASTM D5034

268 lbf warp / 260 lbf weft

ISO 13934-1

1350 N warp / 1390 N weft

Labels



USCG -
EU MRA
0038



STANDARD
100
S21-3365
Hohenstein HTTI

Care & Maintenance



Shrinkage

Shrinkage 70°

-2% warp / -1.5% weft

Colour Connect

7078.01 - 7078.43



7078.01



7078.02



7078.03



7078.04



7078.05



7078.06



7078.07



7078.08



7078.09



7078.10



7078.11



7078.12



7078.13



7078.14



7078.15



7078.16



7078.17



7078.18



7078.19



7078.20



7078.21



7078.22



7078.23



7078.24



7078.25



7078.26



7078.27



7078.28



7078.29



7078.30



7078.31



7078.32



7078.33



7078.34



7078.35



7078.36



7078.37



7078.38



7078.39



7078.40



7078.41



7078.42



7078.43