


Dikson

7063.01 - 7063.14



Produkt

Möbelstoffe

Beschreibung

Üppiger Melange-Möbelstoff aus weichem Chenille-Garn

Zusammensetzung

> **40% recycled polyester FR** / < **60% polyester FR**

Breite

± **140 cm, ± 55 inches**

Gewicht

± **819 gr/m², ± 26 oz/yd²**

Brandschutzklasse

BS 5852 , Crib 5
Cal TB 117-2013, section 1 , Pass
DIN 4102 , B1
EN 1021/1-2 , Pass
IMO 2010 FTP part 8 , Pass
NF P 92/503-507 , M1
NFPA 260 , Class 1

Reibecktheit

ASTM D3597/D4157 (#10 cotton duck) ,
100.000 double rubs Wyzenbeek
ISO 12947-2 , 100.000 rubs Martindale

Pilling

ASTM D3511
5 (scale 1-5)
ISO 12945-2
4-5 (scale 1-5)

Farbechtheit

AATCC 8
4 (scale 1-5) wet / 4 (scale 1-5) dry
ISO 105 X12
4-5 (scale 1-5) wet / 4-5 (scale 1-5) dry

Lichtecktheit

AATCC 16.2 opt.1 or 16.3 opt. 3
4.5 (scale 1-5)
ISO 105 B02
6 (scale 1-8)

Schiebewiderstand

ASTM D4034
89 lbs warp / 96 lbs weft
ISO 13936-2
2 mm warp / 2 mm weft

Reißfestigkeit

ASTM D5034
474 lbs warp / 262 lbs weft
ISO 13934-1
2500 N warp / 1550 N weft

Labels



Pflege & Instandhaltung



Schrumpfung

Shrinkage 30°
-2.6% warp / -1.9% weft

Dikson

7063.01 - 7063.14




7063.01



7063.02



7063.03



7063.04



7063.05



7063.06



7063.07



7063.08



7063.09



7063.10



7063.11



7063.12



7063.13



7063.14