

Dikson

7063.01 - 7063.14



产品

面料

描述

面料系列，由柔软的雪尼尔纱线制成

成分

> 40% recycled polyester FR / < 60% polyester FR

宽幅

± 140 cm, ± 55 inches

重量

± 819 gr/m², ± 26 oz/yd²

阻燃

BS 5852, Crib 5

Cal TB 117-2013, section 1, Pass

DIN 4102, B1

EN 1021/1-2, Pass

IMO 2010 FTP part 8, Pass

NF P 92/503-507, M1

NFPA 260, Class 1

耐磨性

ASTM D3597/D4157 (#10 cotton duck),

100.000 double rubs Wyzenbeek

ISO 12947-2, 100.000 rubs Martindale

起毛指数

ASTM D3511

5 (scale 1-5)

ISO 12945-2

4-5 (scale 1-5)

耐摩擦褪色

AATCC 8

4 (scale 1-5) wet / 4 (scale 1-5) dry

ISO 105 X12

4-5 (scale 1-5) wet / 4-5 (scale 1-5) dry

耐光照褪色

AATCC 16.2 opt.1 or 16.3 opt. 3

4.5 (scale 1-5)

ISO 105 B02

6 (scale 1-8)

耐滑缝

ASTM D4034

89 lbs warp / 96 lbs weft

ISO 13936-2

2 mm warp / 2 mm weft

抗断裂强度

ASTM D5034

474 lbs warp / 262 lbs weft

ISO 13934-1

2500 N warp / 1550 N weft

标签



USCG -
EU MRA
0038



STANDARD
100
507-0023
Hohenstein HTTI

保养与维护



收缩率

Shrinkage 30°

-2.6% warp / -1.9% weft

Dikson

7063.01 - 7063.14




7063.01



7063.02



7063.03



7063.04



7063.05



7063.06



7063.07



7063.08



7063.09



7063.10



7063.11



7063.12



7063.13



7063.14