

Dolin

8048.01 - 8048.09



Product
Curtain

Description
Light textured blend

Composition
100% flame retardant polyester

Width
± 140 cm, ± 55 inches

Weight
± 407 gr/m², ± 13 oz/yd²

Sound absorption
ISO 354, alpha w
0.85 (pleated)

Visual & Thermal comfort
EN 410/EN 14501
Test available

Flame retardancy
BS 5867-2 , Type C
CAN/ULC S109 , Pass
DIN 4102 , B1
EN 13773 , Class 1
IMO 2010 FTP part 7 , Pass
NF P 92/503-507 , M1
NFPA 701 (meth. 1 or 2) , Pass
Übereinstimmung , Pass
UNI VF 8456-8457 , Classe 1

Colorfastness to crocking
AATCC 8 (solids)
5 (scale 1-5) wet / 5 (scale 1-5) dry
ISO 105-X12
4-5 (scale 1-5) wet / 4-5 (scale 1-5) dry

Colorfastness to light
AATCC 16.2 option 1 or 16.3 opt 3
5 (scale 1-5)
ISO 105-B02
6 (scale 1-8)

Seam slippage
ASTM D434
32 lbs warp / 30 lbs weft
ISO 13936-2
5.5 mm warp / 4.7 mm weft

Labels



USCG -
EU MRA
0038



STANDARD
100
S07-0023
Hohenstein HTTI



Baustoffklasse schwerentflammbar
DIN 4102, B1

Care & Maintenance



Shrinkage
Shrinkage 30°
-2% warp / -1% weft
Shrinkage 70°
-2.8% warp / -2% weft

Dolin


8048.01 - 8048.09




8048.01




8048.02




8048.03




8048.04




8048.05




8048.06



8048.07



8048.08



8048.09