

Dolin

8048.01 - 8048.09



Produit

Tissus pour rideaux

Description

Mélangé structuré clair

Composition

100% polyester ignifuge

Largeur

± 140 cm, ± 55 inches

Poids

± 407 gr/m², ± 13 oz/yd²

Absorption acoustique

ISO 354, alpha w

0.85 (pleated)

Confort Visuel & Thermique

EN 410/EN 14501

Test available

Non feu

BS 5867-2 , Type C

CAN/ULC S109 , Pass

DIN 4102 , B1

EN 13773 , Class 1

IMO 2010 FTP part 7 , Pass

NF P 92/503-507 , M1

NFPA 701 (meth. 1 or 2) , Pass

Übereinstimmung , Pass

UNI VF 8456-8457 , Classe 1

Résistance au frottement

AATCC 8 (solids)

5 (scale 1-5) wet / 5 (scale 1-5) dry

ISO 105-X12

4-5 (scale 1-5) wet / 4-5 (scale 1-5) dry

Solidité lumière

AATCC 16.2 option 1 or 16.3 opt 3

5 (scale 1-5)

ISO 105-B02

6 (scale 1-8)

Résistance au glissement à la couture

ASTM D434

32 lbs warp / 30 lbs weft

ISO 13936-2

5.5 mm warp / 4.7 mm weft


Étiquettes



USCG -
EU MRA
0038



STANDARD
100
S07-0023
Hohenstein HTFI



Baustoffklasse schwerentflammbar
DIN 4102, B1

Entretien & Maintenance



Rétrécissement

Shrinkage 30°

-2% warp / -1% weft

Shrinkage 70°


-2.8% warp / -2% weft

Dolin

8048.01 - 8048.09




8048.01




8048.02




8048.03




8048.04




8048.05




8048.06



8048.07



8048.08



8048.09