

Dolin

8048.01 - 8048.09



Product

Gordijnstoffen

Omschrijving

Licht gestructureerde melange

Samenstelling

100% brandvertragend polyester

Breedte

± 140 cm, ± 55 inches

Gewicht

± 407 gr/m¹, ± 13 oz/yd¹

Geluidsabsorptie

ISO 354, alpha w
0.85 (pleated)

Visueel & Thermisch comfort

EN 410/EN 14501

Test available

Brandwerendheid

BS 5867-2 , Type C
CAN/ULC S109 , Pass
DIN 4102 , B1
EN 13773 , Class 1
IMO 2010 FTP part 7 , Pass
NF P 92/503-507 , M1
NFPA 701 (meth. 1 or 2) , Pass
Übereinstimmung , Pass
UNI VF 8456-8457 , Classe 1

Wrijfechtheid

AATCC 8 (solids)

5 (scale 1-5) wet / 5 (scale 1-5) dry

ISO 105-X12

4-5 (scale 1-5) wet / 4-5 (scale 1-5) dry

Lichtecheitheid

AATCC 16.2 option 1 or 16.3 opt 3

5 (scale 1-5)

ISO 105-B02

6 (scale 1-8)

Naadschuifweerstand

ASTM D434

32 lbs warp / 30 lbs weft

ISO 13936-2

5.5 mm warp / 4.7 mm weft


Keurmerken



USCG -
EU MRA
0038



STANDARD
100
S07-0023
Hohenstein HTTI



Baustoffklasse schwerentflammbar
DIN 4102, B1

Reiniging & Onderhoud



Krimp

Shrinkage 30°

-2% warp / -1% weft

Shrinkage 70°

-2.8% warp / -2% weft

Dolin

8048.01 - 8048.09



8048.01



8048.02



8048.03



8048.04



8048.05



8048.06



8048.07



8048.08



8048.09