

Dolin

8048.01 - 8048.09



产品

窗帘

描述

浅色混纺织物

成分

100% 阻燃聚酯纤维

宽幅

± 140 cm, ± 55 inches

重量

± 407 gr/m², ± 13 oz/yd¹

吸声降噪

ISO 354, alpha w

0.85 (pleated)

视觉及热舒适控制

EN 410/EN 14501

Test available

阻燃

BS 5867-2, Type C

CAN/ULC S109, Pass

DIN 4102, B1

EN 13773, Class 1

IMO 2010 FTP part 7, Pass

NF P 92/503-507, M1

NFPA 701 (meth. 1 or 2), Pass

Übereinstimmung, Pass

UNI VF 8456-8457, Classe 1

耐摩擦褪色

AATCC 8 (solids)

5 (scale 1-5) wet / 5 (scale 1-5) dry

ISO 105-X12

4-5 (scale 1-5) wet / 4-5 (scale 1-5) dry

耐光照褪色

AATCC 16.2 option 1 or 16.3 opt 3

5 (scale 1-5)

ISO 105-B02

6 (scale 1-8)

耐滑缝

ASTM D434

32 lbs warp / 30 lbs weft

ISO 13936-2

5.5 mm warp / 4.7 mm weft

标签



USCG -
EU MRA
0038

OEKO
TEX®

STANDARD
100
S07-0023
Hohenstein HTTI



Baustoffklasse schwerentflammbar
DIN 4102, B1

保养与维护



收缩率

Shrinkage 30°

-2% warp / -1% weft

Shrinkage 70°

-2.8% warp / -2% weft

Dolin

8048.01 - 8048.09



8048.01



8048.02



8048.03



8048.04



8048.05



8048.06



8048.07



8048.08



8048.09