

Ellis

8079.01 - 8079.13



Product
Curtain

Description
Soft textured, yarn dyed blend with a non-directional two tonal effect

Composition
100% flame retardant polyester

Width
± 300 cm, ± 118 inches

Weight
± 795 gr/m², ± 26 oz/yd²

Sound absorption
ISO 354, alpha w
0.80 (pleated)

Visual & Thermal comfort
EN 410/EN 14501
Test available

Flame retardancy
BS 5867-2 , Type C
CAN/ULC S109 , Pass
DIN 4102 , B1
EN 13773 , Class 1
IMO 2010 FTP part 7 , Pass
NF P 92/503-507 , M1
NFPA 701 (meth. 1 or 2) , Pass
Übereinstimmung , Pass
UNI VF 8456-8457 , Classe 1

Colorfastness to crocking
AATCC 8 (solids)
5 (scale 1-5) wet / 5 (scale 1-5) dry
ISO 105-X12
4-5 (scale 1-5) wet / 4-5 (scale 1-5) dry

Colorfastness to light
AATCC 16.2 option 1 or 16.3 opt 3
4.5 (scale 1-5)
ISO 105-B02
6 (scale 1-8)

Seam slippage
ASTM D434
47 lbs warp / 47 lbs weft
ISO 13936-2
3.3 mm warp / 3.3 mm weft


Labels



USCG -
EU MRA
0038



STANDARD
100
507-0023
Hohenstein HTTI



Baustoffklasse schwerentflammbar
DIN 4102, B1


Care & Maintenance



Shrinkage
Shrinkage 70°
-2% warp / -2.9% weft

Ellis


8079.01 - 8079.13




8079.01




8079.02




8079.03




8079.04




8079.05




8079.06



8079.07



8079.08



8079.09



8079.10



8079.11



8079.12



8079.13