


Ellis

8079.01 - 8079.13



Product

Curtain

Description

Soft textured, yarn dyed blend with a non-directional two tonal effect

Composition

100% flame retardant polyester

Width

± 300 cm, ± 118 inches

Weight

± 795 gr/m², ± 26 oz/yd²

Sound absorption

ISO 354, alpha w

0.80 (pleated)

Visual & Thermal comfort

EN 410/EN 14501

Test available

Flame retardancy

BS 5867-2 , Type C

CAN/ULC S109 , Pass

DIN 4102 , B1

EN 13773 , Class 1

IMO 2010 FTP part 7 , Pass

NF P 92/503-507 , M1

NFPA 701 (meth. 1 or 2) , Pass

Übereinstimmung , Pass

UNI VF 8456-8457 , Classe 1

Colorfastness to crocking

AATCC 8 (solids)

5 (scale 1-5) wet / 5 (scale 1-5) dry

ISO 105-X12

4-5 (scale 1-5) wet / 4-5 (scale 1-5) dry

Colorfastness to light

AATCC 16.2 option 1 or 16.3 opt 3

4.5 (scale 1-5)

ISO 105-B02

6 (scale 1-8)

Seam slippage

ASTM D434

47 lbs warp / 47 lbs weft

ISO 13936-2

3.3 mm warp / 3.3 mm weft

Labels



USCG -
EU MRA
0038



STANDARD
100
S07-0023
Hohenstein HTTI



Baustoffklasse schwerentflammbar
DIN 4102, B1

Care & Maintenance



Shrinkage

Shrinkage 70°

-2% warp / -2.9% weft

Ellis

8079.01 - 8079.13



8079.01



8079.02



8079.03



8079.04



8079.05



8079.06



8079.07



8079.08



8079.09



8079.10



8079.11



8079.12



8079.13