

# Ellis

8079.01 - 8079.13



## 产品 窗帘

## 描述

纹理柔软，纱线染色混纺出无方向双色调效果

## 成分

100% 阻燃聚酯纤维

## 宽幅

± 300 cm, ± 118 inches

## 重量

± 795 gr/m<sup>2</sup>, ± 26 oz/yd<sup>2</sup>

## 吸声降噪

ISO 354, alpha w  
0.80 (pleated)

## 视觉及热舒适控制

EN 410/EN 14501

Test available

## 阻燃

BS 5867-2, Type C  
CAN/ULC S109, Pass  
DIN 4102, B1  
EN 13773, Class 1  
IMO 2010 FTP part 7, Pass  
NF P 92/503-507, M1  
NFPA 701 (meth. 1 or 2), Pass  
Übereinstimmung, Pass  
UNI VF 8456-8457, Classe 1

## 耐摩擦褪色

AATCC 8 (solids)

5 (scale 1-5) wet / 5 (scale 1-5) dry

ISO 105-X12

4-5 (scale 1-5) wet / 4-5 (scale 1-5) dry

## 耐光照褪色

AATCC 16.2 option 1 or 16.3 opt 3

4.5 (scale 1-5)

ISO 105-B02

6 (scale 1-8)

## 耐滑缝

ASTM D434

47 lbs warp / 47 lbs weft

ISO 13936-2

3.3 mm warp / 3.3 mm weft

## 标签



USCG -  
EU MRA  
0038



STANDARD  
100  
S07-0023  
Hohenstein HTTI



Baustoffklasse schwerentflammbar  
DIN 4102, B1

## 保养与维护



## 收缩率


Shrinkage 70°

-2% warp / -2.9% weft

# Ellis

8079.01 - 8079.13


---




8079.01




8079.02




8079.03




8079.04




8079.05




8079.06



8079.07



8079.08



8079.09



8079.10



8079.11



8079.12



8079.13