

Ellis

8079.01 - 8079.13



产品 窗帘

描述

纹理柔软，纱线染色混纺出无方向双色调效果

成分

100% 阻燃聚酯纤维

宽幅

± 300 cm, ± 118 inches

重量

± 795 gr/m², ± 26 oz/yd²

吸声降噪

ISO 354, alpha w
0.80 (pleated)

视觉及热舒适控制

EN 410/EN 14501
Test available

阻燃

BS 5867-2, Type C
CAN/ULC S109, Pass
DIN 4102, B1
EN 13773, Class 1
IMO 2010 FTP part 7, Pass
NF P 92/503-507, M1
NFPA 701 (meth. 1 or 2), Pass
Übereinstimmung, Pass
UNI VF 8456-8457, Classe 1

耐摩擦褪色

AATCC 8 (solids)
5 (scale 1-5) wet / 5 (scale 1-5) dry

ISO 105-X12

4-5 (scale 1-5) wet / 4-5 (scale 1-5) dry

耐光照褪色

AATCC 16.2 option 1 or 16.3 opt 3

4.5 (scale 1-5)

ISO 105-B02

6 (scale 1-8)

耐滑缝

ASTM D434

47 lbs warp / 47 lbs weft

ISO 13936-2

3.3 mm warp / 3.3 mm weft

标签



USCG -
EU MRA
0038



STANDARD
100
S07-0023
Hohenstein HTI



Vescom B.V.
P.BAY26
170927
Baustoffklasse schwerentflammbar
DIN 4102, B1

保养与维护



收缩率

Shrinkage 70°

-2% warp / -2.9% weft

Ellis

8079.01 - 8079.13



8079.01



8079.02



8079.03



8079.04



8079.05



8079.06



8079.07



8079.08



8079.09



8079.10



8079.11



8079.12



8079.13