

Lamu

7051.01 - 7051.30



Product

Upholstery

Description

Structured felted wool quality

Composition

75% post-consumer recycled wool / 25% polyester

Width

± 150 cm, ± 59 inches

Weight

± 660 gr/m², ± 21 oz/yd²

Flame retardancy

BS 5852 , Crib 5

Cal TB 117-2013, section 1 , Pass

DIN 4102 , B2

EN 1021/1-2 , Pass

IMO 2010 FTP part 8 , Pass

NF P 92/503-507 , M2

NFPA 260 , Class 1

Abrasion

**ASTM D3597/D4157 (#10 cotton duck) ,
>30.000 double rubs Wyzenbeek
ISO 12947-2 , >100.000 rubs Martindale**

Pilling

ASTM D3511

3 (scale 1-5)

ISO 12945-2

4 (scale 1-5)

Colorfastness to crocking

AATCC 8

5 (scale 1-5) wet / 5 (scale 1-5) dry

ISO 105 X12

5 (scale 1-5) wet / 5 (scale 1-5) dry

Colorfastness to light

AATCC 16.2 opt.1 or 16.3 opt. 3

5 (scale 1-5)

ISO 105 B02

5 (scale 1-8)

Seam slippage

ASTM D4034

26 lbf warp / 26 lbf weft

ISO 13936-2

3.5 mm warp / 3.5 mm weft

Breaking strength

ASTM D5034

73 lbs warp / 76 lbs weft

Labels



USCG -
EU MRA
0038




STANDARD
100
519-3058
Hohenstein HTTI

Care & Maintenance



Lamu

7051.01 - 7051.30




7051.01




7051.02




7051.03




7051.04




7051.05



7051.06



7051.07



7051.08




7051.09



7051.10




7051.11



7051.12



7051.13




7051.14



7051.15



7051.16



7051.17



7051.18




7051.19




7051.20



7051.21




7051.22




7051.23




7051.24




7051.25



7051.26



7051.27



7051.28



7051.29



7051.30