

Lani

7060.01 - 7060.56



Product

Upholstery

Description

Tough, felted wool quality in modern applicable colours

Composition

80% wool / 20% polyamide

Width

± 140 cm, ± 55 inches

Weight

± 640 gr/m², ± 21 oz/yd²

Flame retardancy

**BS 5852 , Crib 5 with FR finish
Cal TB 117-2013, section 1 , Pass
DIN 4102 , B2 with FR finish
EN 1021/1-2 , Pass
IMO 2010 FTP part 8 , Pass with FR finish
NF P 92/503-507 , M2 with FR finish
NFPA 260 , Class 1
UNI 9175 , Classe 1 with FR finish**

Abrasion

**ASTM D3597/D4157 (#10 cotton duck) ,
100.000 double rubs Wyzenbeek
ISO 12947-2 , >300.000 rubs Martindale**

Pilling

**ASTM D3511
2.5 (scale 1-5)
ISO 12945-2
4 (scale 1-5)**

Colorfastness to crocking

**AATCC 8
5 (scale 1-5) wet / 5 (scale 1-5) dry
ISO 105 X12
4 - 5 (scale 1-5) wet / 4 - 5 (scale 1-5) dry**

Colorfastness to light

**AATCC 16.2 opt.1 or 16.3 opt. 3
3.5 (scale 1-5)
ISO 105 B02
5-7 (scale 1-8)**

Seam slippage

**ASTM D4034
125 lbs warp / 116 lbs weft
ISO 13936-2
2.6 mm warp / 3 mm weft**

Breaking strength

**ASTM D5034
206 lbs warp / 202 lbs weft**

Labels



Care & Maintenance



Lani

7060.01 - 7060.56

