

Lani

7060.01 - 7060.56



Product

Upholstery

Description

Tough, felted wool quality in modern applicable colours

Composition

80% wool / 20% polyamide

Width

± 140 cm, ± 55 inches

Weight

± 640 gr/m¹, ± 21 oz/yd¹

Flame retardancy

**BS 5852 , Crib 5 with FR finish
Cal TB 117-2013, section 1 , Pass
DIN 4102 , B2 with FR finish
EN 1021/1-2 , Pass
IMO 2010 FTP part 8 , Pass with FR finish
NF P 92/503-507 , M2 with FR finish
NFPA 260 , Class 1
UNI 9175 , Classe 1 with FR finish**

Abrasion

**ASTM D3597/D4157 (#10 cotton duck) ,
100.000 double rubs Wyzenbeek
ISO 12947-2 , >300.000 rubs Martindale**

Pilling

**ASTM D3511
2.5 (scale 1-5)
ISO 12945-2
4 (scale 1-5)**

Colorfastness to crocking

AATCC 8

5 (scale 1-5) wet / 5 (scale 1-5) dry

ISO 105 X12

4 - 5 (scale 1-5) wet / 4 - 5 (scale 1-5) dry

Colorfastness to light

AATCC 16.2 opt.1 or 16.3 opt. 3

3.5 (scale 1-5)

ISO 105 B02

5-7 (scale 1-8)

Seam slippage

ASTM D4034

125 lbs warp / 116 lbs weft

ISO 13936-2

2.6 mm warp / 3 mm weft

Breaking strength

ASTM D5034

206 lbs warp / 202 lbs weft

Labels



USCG -
EU MRA
0038



STANDARD
100
S10-0100
Hohenstein RTTI

Care & Maintenance



Lani

7060.01 - 7060.56



7060.01



7060.02



7060.03



7060.04



7060.05



7060.06



7060.07



7060.08



7060.09



7060.10



7060.11



7060.12



7060.13



7060.14



7060.15



7060.16



7060.17



7060.18



7060.19



7060.20



7060.21



7060.22



7060.23



7060.24



7060.25



7060.26



7060.27



7060.28



7060.29



7060.30



7060.31



7060.32



7060.33



7060.34



7060.35



7060.36



7060.37



7060.38



7060.39



7060.40



7060.41



7060.42



7060.43



7060.44



7060.45



7060.46



7060.47



7060.48



7060.49



7060.50



7060.51



7060.52



7060.53



7060.54



7060.55



7060.56