

Mioko

8057.01 - 8057.33



Product
Curtain

Description
Unpatterned satin

Composition
100% flame retardant polyester

Width
± 140 cm, ± 56 inches

Weight
± 413 gr/m², ± 12 oz/yd²

Visual & Thermal comfort
EN 410/EN 14501
Test available

Flame retardancy
BS 5867-2 , Type C
CAN/ULC S109 , Pass
DIN 4102 , B1
EN 13773 , Class 1
IMO 2010 FTP part 7 , Pass
NF P 92/503-507 , M1
NFPA 701 (meth. 1 or 2) , Pass
Übereinstimmung , Pass
UNI VF 8456-8457 , Classe 1

Colorfastness to crocking
AATCC 8 (solids)
5 (scale 1-5) wet / 5 (scale 1-5) dry
ISO 105-X12
5 (scale 1-5) wet / 5 (scale 1-5) dry

Colorfastness to light
AATCC 16.2 option 1 or 16.3 opt 3
5 (scale 1-5)
ISO 105-B02
6-7 (scale 1-8)

Seam slippage
ASTM D434
45.5 lbs warp / 40.5 lbs weft


Labels



USCG -
EU MRA
0038



STANDARD
100
507-0023
Hohenstein HTTI



Baustoffklasse schwerenflammbar
DIN 4102, B1

Care & Maintenance



Shrinkage
Shrinkage 30°
-1% warp / -0.4% weft
Shrinkage 70°
-1.7% warp / -0.6% weft

Mioko

8057.01 - 8057.33

