

# Noss

7058.01 - 7058.24



## Product

### Upholstery

## Description

**Woven chenille blended in soft colours**

## Composition

**22% recycled polyester FR / 78% polyester FR**

## Width

**± 140 cm, ± 55 inches**

## Weight

**± 904 gr/m<sup>2</sup>, ± 29 oz/yd<sup>2</sup>**

## Flame retardancy

**BS 5852 , Crib 5**

**Cal TB 117-2013, section 1 , Pass**

**DIN 4102 , B1**

**EN 1021/1-2 , Pass**

**IMO 2010 FTP part 8 , Pass**

**NF P 92/503-507 , M1**

**NFPA 260 , Class 1**

## Abrasion

**ASTM D3597/D4157 (#10 cotton duck) ,**

**90.000 double rubs Wyzenbeek**

**ISO 12947-2 , 70.000 rubs Martindale**

## Pilling

**ASTM D3511**

5 (scale 1-5)

**ISO 12945-2**

4 (scale 1-5)

## Colorfastness to crocking

**AATCC 8**

5 (scale 1-5) wet / 5 (scale 1-5) dry

**ISO 105 X12**

4 - 5 (scale 1-5) wet / 4 - 5 (scale 1-5) dry

## Colorfastness to light

**AATCC 16.2 opt.1 or 16.3 opt. 3**

5 (scale 1-5)

**ISO 105 B02**

6 - 7 (scale 1-8)

## Seam slippage

**ASTM D4034**

77 lbs warp / 91 lbs weft

**ISO 13936-2**

3.3 mm warp / 3 mm weft

## Breaking strength

**ASTM D5034**

524 lbs warp / 337 lbs weft

## Labels



USCG -  
EU MRA  
0038



STANDARD  
100  
507-0023  
Hohenstein HTTI

## Care & Maintenance



## Shrinkage

**Shrinkage 30°**

-1.5% warp / -1.7% weft


**Shrinkage 70°**

-1.6% warp / -3% weft

# Noss

7058.01 - 7058.24

---




7058.01




7058.02



7058.03




7058.04




7058.05




7058.06



7058.07



7058.08



7058.09



7058.10



7058.11



7058.12



7058.13



7058.14



7058.15



7058.16



7058.17



7058.18



7058.19



7058.20



7058.21



7058.22



7058.23



7058.24