

Rani

8067.01 - 8067.22



Produkt

Vorhangstoffe

Beschreibung

Vorhangstoff in Leinenoptik, Dim-Out

Zusammensetzung

100% schwer entflammbares Polyester

Breite

± 294 cm, ± 116 inches

Gewicht

± 861 gr/m¹, ± 28 oz/yd¹

Schallabsorption

**ISO 354, alpha w
0.70**

Visueller und thermischer Komfort

AATCC 148

Test available

EN 410/EN 14501

Test available

Brandschutzklasse

BS 5867-2 , Type C

CAN/ULC S109 , Pass

DIN 4102 , B1

EN 13773 , Class 1

IMO 2010 FTP part 7 , Pass

NF P 92/503-507 , M1

NFPA 701 (meth. 1 or 2) , Pass

Übereinstimmung , Pass

UNI VF 8456-8457 , Classe 1

Farbechtheit

AATCC 8 (solids)

5 (scale 1-5) wet / 5 (scale 1-5) dry

ISO 105-X12

4-5 (scale 1-5) wet / 4-5 (scale 1-5) dry

Lichtechtheit

AATCC 16.2 option 1 or 16.3 opt 3

2.5 (scale 1-5)

ISO 105-B02

5 (scale 1-8)

Schiebewiderstand

ASTM D434

53.5 lbs warp / 48 lbs weft


Labels



USCG -
EU MRA
0038



STANDARD
100
507-0023
Hohenstein HTTI



Baustoffklasse schwerentflammbar
DIN 4102, B1

Pflege & Instandhaltung



Schrumpfung

Shrinkage 30°

-0.8% warp / -0.4% weft

Shrinkage 70°

-1.6% warp / -0.7% weft

Rani

8067.01 - 8067.22



8067.01



8067.02



8067.03



8067.04



8067.05



8067.06



8067.07



8067.08



8067.09



8067.10



8067.11



8067.12



8067.13



8067.14



8067.15



8067.16



8067.17



8067.18



8067.19



8067.20



8067.21



8067.22