

Rolla

7065.01 - 7065.20



Product

Upholstery

Description

Upholstery fabric with a bold 3D graphic pattern

Composition

88% recycled polyester FR / 12% polyester FR

Width

± 140 cm, ± 55 inches

Weight

± 775 gr/m², ± 25 oz/yd²

Flame retardancy

EN 1021/1-2 , Pass

BS 5852 , Crib 5

NF P 92/503-507 or NF D 60-013 , M1

DIN 4102 , B1

Cal TB 117-2013, section 1 , Pass

IMO 2010 FTP part 8 , Pass

NFPA 260 , Class 1

Abrasion

ISO 12947-2 , 50.000 rubs Martindale

ASTM D3597/D4157 (#10 cotton duck) , 100.000 double rubs Wyzenbeek

Pilling

ISO 12945-2

4 (scale 1-5)

ASTM D3511

3 (scale 1-5)

Colorfastness to crocking

ISO 105 X12

wet 4-5 (scale 1-5) / dry 4-5 (scale 1-5)

AATCC 8

wet 5 (scale 1-5) / dry 4.5 (scale 1-5)

Colorfastness to light

ISO 105 B02

6 (scale 1-8)

AATCC 16.2 opt.1 or 16.3 opt. 3

4 (scale 1-5)

Seam slippage

ISO 13936-2

warp 2.3 mm / weft 2 mm

ASTM D4034

warp 102 lbs / weft 83 lbs

Breaking strength

ISO 13934-1

warp 1120 N / weft 2500 N

ASTM D5034

warp 239 lbs / weft 560 lbs

Labels



USCG -
EU MRA
0038



STANDARD
100
507-0023
Hohenstein HTTI

Care & Maintenance



Shrinkage


Shrinkage 70° warp -2.8% / weft -2.6%

Rolla


7065.01 - 7065.20




7065.01




7065.02



7065.03




7065.04



7065.05




7065.06



7065.07




7065.08



7065.09



7065.10




7065.11



7065.12




7065.13



7065.14




7065.16



7065.17



7065.18



7065.19



7065.20



7065.15