

Tula

8081.01 - 8081.16



Product

Curtain

Description

Subtle coloured melange structure in a dry wooly look and feel

Composition

60% recycled polyester FR / 40% polyester FR

Width

± 149 cm, ± 59 inches

Weight

± 395 gr/m², ± 13 oz/yd²

Sound absorption

ISO 354, alpha w
0.75 (pleated)

Visual & Thermal comfort

EN 410/EN 14501

Test available

Flame retardancy

BS 5867-2 , Type C
CAN/ULC S109 , Pass
DIN 4102 , B1
EN 13773 , Class 1
IMO 2010 FTP part 7 , Pass
NF P 92/503-507 , M1
NFPA 701 (meth. 1 or 2) , Pass
Übereinstimmung , Pass
UNI VF 8456-8457 , Classe 1

Colorfastness to crocking

AATCC 8 (solids)

5 (scale 1-5) wet / 5 (scale 1-5) dry

ISO 105-X12

4-5 (scale 1-5) wet / 4-5 (scale 1-5) dry

Colorfastness to light

AATCC 16.2 option 1 or 16.3 opt 3

5 (scale 1-5)

ISO 105-B02

6 (scale 1-8)

Seam slippage

ASTM D434

49 lbs warp / 51 lbs weft

ISO 13936-2

3 mm warp / 4.7 mm weft

Labels



USCG -
EU MRA
0038



STANDARD
100
S07-0023
Hohenstein HTFI



Vescom B.V.
P.BAY26
170927
Baustoffklasse schwerentflammbar
DIN 4102, B1

Care & Maintenance



Shrinkage

Shrinkage 70°

-2% warp / -1.6% weft

Tula

8081.01 - 8081.16



8081.01



8081.02



8081.03



8081.04



8081.05



8081.06



8081.07



8081.08



8081.09



8081.10



8081.11



8081.12



8081.13



8081.14



8081.15



8081.16