

# Tula

8081.01 - 8081.16



**Product**  
**Curtain**

**Description**

**Subtle coloured melange structure in a dry wooly look and feel**

**Composition**

**60% recycled polyester FR / 40% polyester FR**

**Width**

**± 149 cm, ± 59 inches**

**Weight**

**± 395 gr/m<sup>2</sup>, ± 13 oz/yd<sup>2</sup>**

**Sound absorption**

**ISO 354, alpha w**  
0.75 (pleated)

**Visual & Thermal comfort**

**EN 410/EN 14501**

Test available

**Flame retardancy**

**BS 5867-2 , Type C**  
**CAN/ULC S109 , Pass**  
**DIN 4102 , B1**  
**EN 13773 , Class 1**  
**IMO 2010 FTP part 7 , Pass**  
**NF P 92/503-507 , M1**  
**NFPA 701 (meth. 1 or 2) , Pass**  
**Übereinstimmung , Pass**  
**UNI VF 8456-8457 , Classe 1**

**Colorfastness to crocking**

**AATCC 8 (solids)**

5 (scale 1-5) wet / 5 (scale 1-5) dry

**ISO 105-X12**

4-5 (scale 1-5) wet / 4-5 (scale 1-5) dry

**Colorfastness to light**

**AATCC 16.2 option 1 or 16.3 opt 3**

5 (scale 1-5)

**ISO 105-B02**

6 (scale 1-8)

**Seam slippage**

**ASTM D434**

49 lbs warp / 51 lbs weft

**ISO 13936-2**

3 mm warp / 4.7 mm weft


**Labels**



USCG -  
EU MRA  
0038



STANDARD  
100  
S07-0023  
Hohenstein HTTI



Baustoffklasse schwerentflammbar  
DIN 4102, B1

**Care & Maintenance**



**Shrinkage**


**Shrinkage 70°**

-2% warp / -1.6% weft


# Tula

8081.01 - 8081.16

---




8081.01




8081.02



8081.03




8081.04



8081.05




8081.06



8081.07



8081.08



8081.09




8081.10



8081.11



8081.12



8081.13



8081.14



8081.15



8081.16