

Tula

8081.01 - 8081.16



Product
Curtain

Description
Subtle coloured melange structure in a dry wooly look and feel

Composition
100% flame retardant polyester

Width
± 149 cm, ± 59 inches

Weight
± 395 gr/m², ± 13 oz/yd²

Sound absorption
ISO 354, alpha w
0.75 (pleated)

Visual & Thermal comfort
EN 410/EN 14501
Test available

Flame retardancy
BS 5867-2 , Type C
CAN/ULC S109 , Pass
DIN 4102 , B1
EN 13773 , Class 1
IMO 2010 FTP part 7 , Pass
NF P 92/503-507 , M1
NFPA 701 (meth. 1 or 2) , Pass
Übereinstimmung , Pass
UNI VF 8456-8457 , Classe 1

Colorfastness to crocking
AATCC 8 (solids)
5 (scale 1-5) wet / 5 (scale 1-5) dry
ISO 105-X12
4-5 (scale 1-5) wet / 4-5 (scale 1-5) dry

Colorfastness to light
AATCC 16.2 option 1 or 16.3 opt 3
5 (scale 1-5)
ISO 105-B02
6 (scale 1-8)

Seam slippage
ASTM D434
49 lbs warp / 51 lbs weft
ISO 13936-2
3 mm warp / 4.7 mm weft

Labels



USCG -
EU MRA
0038



STANDARD
100
S07-0023
Hohenstein HTTI



Baustoffklasse schwerentflammbar
DIN 4102, B1

Care & Maintenance



Shrinkage
Shrinkage 70°
-2% warp / -1.6% weft

Tula

8081.01 - 8081.16




8081.01



8081.02



8081.03




8081.04



8081.05




8081.06




8081.07




8081.08




8081.09




8081.10




8081.11



8081.12




8081.13



8081.14



8081.15



8081.16